





TYCOON – THE INTELLIGENCE OF LIGHTING.

LIGHTING COMPONENTS FOR COMPLEX OFFICE CONCEPTS AND INDIVIDUAL REQUIREMENTS.

Light needs structure. Lighting designs and structures rooms. Light affects the appearance of an office and influences people's wellbeing, motivation and performance. The synergy and interaction of material, color, form, proportions and light is vital.

Light plays a key role. The aim of the ideal office lighting is to supply intelligent light that is able to adjust to your needs and support the people using it.

Intelligent lighting must fully satisfy these requirements and feature a future oriented design.

TYCOON luminaires emphasize this intelligence because they feature innovative light control, highly effective glare-free technology and extensive energy-saving potential. They are user-friendly and environmentally friendly, safe and standard-compliant.

TYCOON – for high lighting quality and maximum lighting efficiency in the office



TYCOON – A DESIGN RANGE FOR A WIDE VARIETY OF LIGHTING CONCEPTS.

INDIRECT-DIRECT LUMINAIRES WITH A UNIFORM DESIGN.

Holistic thinking and optimization. Intelligent TWIN-C lighting concepts by Waldmann provide the balance of energy efficiency and lighting comfort. The focus is not placed on the complete illumination of the room, but on the best and most economical illumination for a person's workplace.

TYCOON luminaires are the supporting pillars of a TWIN-C concept. The aim of working more economically in future is supported by TYCOON luminaires in cubicles, open-space offices, corridors or conference rooms. The indirect-direct luminaires combine the efficiency of direct lighting with the pleasant ceiling illumination by indirect light.

Waldmann's TYCOON product family presents a wide range of free-standing, suspended, surface-mounted and wall-mounted luminaires. It combines intelligent and innovative technology, efficient lamp technology and contemporary design. With their clear forms and uniform appearance, TYCOON luminaires can be subtly and discreetly integrated in any kind of architecture.



TYCOON – FREE-STANDING AND DESK-MOUNTED LUMINAIRES.

INTELLIGENCE MAKES LIFE EASY.





Intelligent cleaning and maintenance

Without tools, the side parts can be removed and the screen can be extracted. Subsequently, the lamps can be easily removed or the screen can be wiped clean.



Intelligent operation

The operating element is situated at working height. You can reach it without standing up. It is extremely easy to operate and shows you the current output of your TYCOON. The communication with switchable sockets is also possible.



Intelligent desk connection

Saves space and costs. TYCOON desk-mounted luminaires – integrative, variable connection options of the luminaire to the furniture.



Intelligent ergonomics

The branched foot – outstanding stability combined with cleverly devised ergonomics. If table legs are in the way, just push the luminaire closer to you.

TYCOON – FREE-STANDING AND DESK-MOUNTED LUMINAIRES.

INTELLIGENT ENERGY EFFICIENCY INTEGRATED AS STANDARD.

Save energy, not light. You can reach this goal with high-quality TYCOON free-standing luminaires with the integrated light management system Waldmann PULSE.

Practice has shown: Daylight and presence sensors cut your energy costs by up to 50%. The light is only switched on if the sensor registers a presence in the room and the daylight is no longer sufficient. The users hardly notice the luminaires being switched on and off because the light is slowly brightened and dimmed. Furthermore, the sensor regulates the amount of lighting based on the level of daylight.

In combination with KNX or LON components, TYCOON PULSE HFMD becomes part of an intelligent building and exchanges information with other systems.

The light management system PULSE is available with both the fine-tuned high-frequency sensor HFMD and the passive infrared sensor. It creates the best prerequisites for the fulfillment of the European Energy Efficiency Directive and for the even stricter Swiss Minergie requirements.

Particularly energy-optimized TYCOON luminaires with a high lighting quality are also awarded the Waldmann title efficient light.



efficient *light*



PULSE PIR



PULSE HFMD





TYCOON – PENDANT UPLIGHTERS.

THE SOLUTION FOR FLEXIBLE ROOM CONCEPTS.

TYCOON pendant uplighters are a highly intelligent contribution to increasing energy efficiency. With their light-amplifying micro prism and high-gloss reflectors, they generate efficiency of more than 90%. This means: you need fewer luminaires. A 'bright spot' that will have a positive effect on your procurement costs.

Even in operation, you can cut costs. Fitted with an intelligent light management system, TYCOON pendant uplighters control the amount of lighting based on the percentage of daylight and your presence. A further convenience: The luminaires can be controlled by using battery-free wireless technology.

TYCOON pendant uplighters score highly with projects in terms of their flexibility. The all-round glare control achieved by the use of a micro prism enables an axis-oriented positioning of the luminaire – so at a 90° angle to the window front and directly above the workplaces. This gives you flexibility for your future planning. Room divisions can be changed any way you like and dividing walls are easier to position. Fitted with a multiwatt electronic ballast, TYCOON pendant uplighters allow the optional use of 28 W or 54 W lamps. The lighting level can also be adjusted to changes in room or workplace requirements.




TECHNICAL DATA

TYCOON COMFORT FREE-STANDING AND DESK-MOUNTED LUMINAIRES

FOUR-FLAME STRAIGHT POLE



efficient *light*



Free-standing luminaire/Desk-mounted luminaire

CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	4 x compact fluorescent lamps TC-L 55 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 235 W
MAINS LEAD	approx. 3 m; shock-proof plug
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
TUBULAR SECTION	steel tube silver metallic paint, straight
BASE	rectangular steel sheet, flat, silver metallic paint
OPERATION	multifunction button in the tubular section
LUMINAIRE EFFICIENCY	72 %
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 27 %
GLARE PROTECTION	light-amplifying micro prism, medium luminance on the reflector in accordance with the EN 12464-1 specifications
LAMP COVER	none

SPECIAL FEATURES

- Integrated light and presence sensor PULSE HFMD
- Sensitive response; pleasant, inconspicuous control and dimming behaviour thanks to appropriate impulse delay and asymmetrical dimming of PULSE HFMD
- Two individually adjustable lighting levels
- Easy to reach, multifunctional operating element (can be connected to switched power sockets)
- Luminaire head can be rotated by +/- 90°
- Removable side part and screen for easy changing of lamps and easy cleaning

ORDER NUMBERS

FREE-STANDING LUMINAIRES TYPE FITTED WITH ORDER NUMBER

UPRIGHT TUBULAR SECTION

Free-standing luminaire switchable	DUP 455/2	4 x 55 W	121 245 008
Free-standing luminaire dimmable	DUP 455/D	4 x 55 W	121 248 008
Free-standing luminaire PULSE HFMD	DYS 455/P	4 x 55 W	121 250 008

DESK-MOUNTED LUMINAIRES TYPE FITTED WITH ORDER NUMBER

STRAIGHT TUBULAR SECTION


Desk-mounted luminaire switchable	DUP 455/2	4 x 55 W	121 256 008
Desk-mounted luminaire dimmable	DUP 455/D	4 x 55 W	121 258 008
Desk-mounted luminaire PULSE HFMD	DYS 455/P	4 x 55 W	121 260 008

ACCESSORIES


ORDER NUMBER

DESK-MOUNTED LUMINAIRES

Table clamp black, Span 20 mm – 28 mm (Further adaptations available on request)	191 102 019
--	-------------



Free-standing luminaire



Desk-mounted luminaire


TECHNICAL DATA

TYCOON COMFORT FREE-STANDING AND DESK-MOUNTED LUMINAIRES

FOUR-FLAME BENT POLE



efficient^{light}




Free-standing luminaire/Desk-mounted luminaire

CONNECTED LOAD	230 – 240V; 50/60Hz
FITTED WITH	4 x compact fluorescent lamps TC-L 55 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 235 W
MAINS LEAD	approx. 3 m; shock-proof plug
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
TUBULAR SECTION	steel tube silver metallic paint, offset
BASE	c-shaped steel sheet, flat, silver metallic paint
OPERATION	multifunction button in the tubular section
LUMINAIRE EFFICIENCY	72 %
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 27 %
GLARE PROTECTION	light-amplifying micro prism, medium luminance on the reflector in accordance with the EN 12464-1 specifications
LAMP COVER	none


SPECIAL FEATURES

- Integrated light and presence sensor PULSE HFMD
- Sensitive response; pleasant, inconspicuous control and dimming behaviour thanks to appropriate impulse delay and asymmetrical dimming of PULSE HFMD
- Two individually adjustable lighting levels
- Easy to reach, multifunctional operating element (can be connected to switched power sockets)
- Luminaire head can be rotated by +/- 90°
- Removable side part and screen for easy changing of lamps and easy cleaning
- Head connection can be rotated to an angle of +/- 45°
- Integrated EIB/KNX or LON component (for Type DYS 455/PB)

ORDER NUMBERS



Free-standing luminaire



Desk-mounted luminaire

FREE-STANDING LUMINAIRES TYPE FITTED WITH ORDER NUMBER

OFFSET TUBULAR SECTION

Free-standing luminaire switchable	DUP 455/2	4 x 55 W	121 384 008
Free-standing luminaire dimmable	DUP 455/D	4 x 55 W	121 385 008
Free-standing luminaire dimmable, DALI	DUP 455/D	4 x 55 W	121 387 008
Free-standing luminaire PULSE HFMD	DYS 455/P	4 x 55 W	121 386 008
Free-standing luminaire PULSE EIB/KNX	DYS 455/PB	4 x 55 W	121 469 008
Free-standing luminaire PULSE LION	DYS 455/PB	4 x 55 W	On request

DESK-MOUNTED LUMINAIRES TYPE FITTED WITH ORDER NUMBER

OFFSET TUBULAR SECTION

Desk-mounted luminaire switchable	DUP 455/2	4 x 55 W	121 391 008
Desk-mounted luminaire dimmable	DUP 455/D	4 x 55 W	121 392 008
Desk-mounted luminaire PULSE HFMD	DYT 455/P	4 x 55 W	121 393 008

ACCESSORIES

ORDER NUMBER

FREE-STANDING LUMINAIRE PULSE EIB/LON/DALI:	Data line with RJ 45 plug	210 218 019
	Power supply cord shock-proof plug	330 293 020


DESK-MOUNTED LUMINAIRES:

Table clamp black, Span 20 mm – 28 mm	191 102 019
(Further adaptations available on request)	

TECHNICAL DATA

TYCOON COMFORT FREE-STANDING AND DESK-MOUNTED LUMINAIRES

TWO-FLAME STRAIGHT POLE




Free-standing luminaire/Desk-mounted luminaire

CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	2 x compact fluorescent lamps TC-L 55 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 114 W
MAINS LEAD	approx. 3 m; shock-proof plug
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
TUBULAR SECTION	steel tube silver metallic paint, straight
BASE	rectangular steel sheet, flat, silver metallic paint
OPERATION	multifunction button in the tubular section
LUMINAIRE EFFICIENCY	72 %
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 27 %
GLARE PROTECTION	light-amplifying micro prism, medium luminance on the reflector in accordance with the EN 12464-1 specifications
LAMP COVER	None


SPECIAL FEATURES

- Integrated light and presence sensor PULSE HFMD
- Sensitive response; pleasant, inconspicuous control and dimming behaviour thanks to appropriate impulse delay and asymmetrical dimming of PULSE HFMD
- Two individually adjustable lighting levels
- Easy to reach, multifunctional operating element (can be connected to switched power sockets)
- Luminaire head can be rotated by +/- 90°
- Removable side part and screen for easy changing of lamps and easy cleaning

ORDER NUMBERS



Free-standing luminaire



Desk-mounted luminaire

FREE-STANDING LUMINAIRES TYPE FITTED WITH ORDER NUMBER

Free-standing luminaire switchable	DYS 255	2 x 55 W	121 438 008
Free-standing luminaire dimmable	DUP 255/D	2 x 55 W	121 437 008
Free-standing luminaire PULSE HFMD	DYS 255/P	2 x 55 W	121 436 008

DESK-MOUNTED LUMINAIRES TYPE FITTED WITH ORDER NUMBER

Desk-mounted luminaire switchable	DYT 255	2 x 55 W	121 448 008
Desk-mounted luminaire dimmable	DUP 255/D	2 x 55 W	121 447 008
Desk-mounted luminaire PULSE HFMD	DYT 255/P	2 x 55 W	121 446 008

ACCESSORIES ORDER NUMBER

DESK-MOUNTED LUMINAIRES:	Table clamp black, Span 20 mm – 28 mm	191 102 019
	(Further adaptations available on request)	

TECHNICAL DATA

TYCOON CLASSIC FREE-STANDING AND DESK-MOUNTED LUMINAIRES


TWO- AND FOUR-FLAME STRAIGHT POLE



CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	2 x/4 x compact fluorescent lamps TC-L 55 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 114 W/235 W
MAINS LEAD	approx. 3 m; shock-proof plug
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
TUBULAR SECTION	steel tube silver metallic paint, straight
BASE	rectangular steel sheet, flat, silver metallic paint
OPERATION	switch in the luminaire head
LUMINAIRE EFFICIENCY	68 %
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 17 %, indirect proportion approx. 83 %
GLARE PROTECTION	fine-louvre element
LAMP COVER	none


SPECIAL FEATURES

- Integrated light sensor and motion detector PULSE PIR
- Two individually adjustable lighting levels
- Luminaire head can be rotated by +/- 90°
- Removable side part and fine-louvre element for easy changing of lamps and easy cleaning
- Integrated EnOcean wireless technology 868MHz, lighting level can be set wirelessly (type DF)




Two-flame Four-flame
Free-standing luminaire/Desk-mounted luminaire

ORDER NUMBERS



Two-flame Four-flame
Free-standing luminaire



Two-flame Four-flame
Desk-mounted luminaire

FREE-STANDING LUMINAIRES

	TYPE	FITTED WITH	ORDER NUMBER
Free-standing luminaire switchable	LYS 255	2 x 55 W	121 441 008
Free-standing luminaire dimmable	LYS 255/D	2 x 55 W	121 440 008
Free-standing luminaire PULSE PIR	LYS 255/R	2 x 55 W	121 439 008
Free-standing luminaire switchable	LYS 455/2	4 x 55 W	121 370 008
Free-standing luminaire dimmable	LYS 455/D	4 x 55 W	121 371 008
Free-standing luminaire wireless dimming	LYS 455/DF	4 x 55 W	121 371 017
Free-standing luminaire PULSE PIR	LYS 455/R	4 x 55 W	121 372 008
Free-standing luminaire dimmable, DALI	LYS 455/D	4 x 55 W	121 373 008

DESK-MOUNTED LUMINAIRES

	TYPE	FITTED WITH	ORDER NUMBER
Desk-mounted luminaire switchable	LYT 255	2 x 55 W	121 451 009
Desk-mounted luminaire dimmable	LYT 255/D	2 x 55 W	121 450 008
Desk-mounted luminaire PULSE PIR	LYT 255/R	2 x 55 W	121 449 008
Desk-mounted luminaire switchable	LYT 455	4 x 55 W	121 377 008
Desk-mounted luminaire dimmable	LYT 455/D	4 x 55 W	121 378 008
Desk-mounted luminaire PULSE PIR	LYT 455/R	4 x 55 W	121 379 008


ACCESSORIES

	ORDER NUMBER
DESK-MOUNTED LUMINAIRES:	
Table clamp black,	
Span 20 mm – 28 mm	191 102 019
(Further adaptations available on request)	
FREE-STANDING LUMINAIRE WIRELESS DIMMING:	
Battery-free wall transmitter	330 633 010

TECHNICAL DATA

TYCOON COMFORT FREE-STANDING LUMINAIRE T5 VARIANT

TWO-FLAME STRAIGHT POLE


efficient *light*

Free-standing luminaire

CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	2 x fluorescent lamps T5 28/54 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 63 W/119 W
MAINS LEAD	approx. 3 m; shock-proof plug
MATERIAL HOUSING	steel/Aluminum/Plastic, painted silver metallic
TUBULAR SECTION	steel tube silver metallic paint, straight
BASE	rectangular steel sheet, flat, silver metallic paint
OPERATION	multifunction button in the tubular section
LUMINAIRE EFFICIENCY	with cover 94 % /90 %
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 35 %
GLARE PROTECTION	light-amplifying micro prism, medium Luminance on the reflector in accordance with EN 12464
LAMP COVER	acrylic, clear

SPECIAL FEATURES

- Integrated light and presence sensor PULSE PIR
- Sensitive response; pleasant, inconspicuous control and dimming behaviour thanks to appropriate impulse delay and asymmetrical dimming of PULSE HFMD
- Two individually adjustable lighting levels
- Easy to reach, multifunctional operating element (can be connected to switched power sockets)
- Removable side part and screen for easy changing of lamps and easy cleaning

ORDER NUMBERS

Free-standing luminaire


FREE-STANDING LUMINAIRES TYPE FITTED WITH ORDER NUMBER

Free-standing luminaire switchable	DYS 228	2 x 28 W	121 559 008
Free-standing luminaire dimmable	DYS 228/D	2 x 28 W	121 559 009
Free-standing luminaire PULSE PIR	DYS 228/R	2 x 28 W	121 559 010
Free-standing luminaire switchable	DYS 254	2 x 54 W	121 560 008
Free-standing luminaire dimmable	DYS 254/D	2 x 54 W	121 560 009
Free-standing luminaire PULSE PIR	DYS 254/R	2 x 54 W	121 560 010

TECHNICAL DATA

TYCOON COMFORT PENDANT UPLIGHTER

TWO- AND FOUR-FLAME




Pendant uplighter

CONNECTED LOAD	230 – -240 V; 50/60 Hz
FITTED WITH	2 x/4 x fluorescent lamps T16 28 W, 35 W/54 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 63 W, 79 W/119 W or 126 W/238 W
MAINS LEAD	approx. 1.0 m; with free stranded wires
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
FASTENING	steel cord 0.3 m – 0.7 m
OPERATION	switch, button, DALI, wireless
LUMINAIRE EFFICIENCY	with cover 94 % (28 W, 35 W)/90 % (54 W)
LIGHT DISTRIBUTION	symmetrical; direct proportion approx. 35 %
GLARE PROTECTION	light-amplifying micro prism, medium luminance on the reflector in accordance with EN 12464
LAMP COVER	acrylic, clear


SPECIAL FEATURES

- Very high efficiency of > 90 % thanks to innovative light technology
- Depending on the room coordinates, consumption of < 10 W per m² can be generated
- The standard-compliant all-round glare control enables the luminaire to be positioned directly above workplaces and at an angle to the windows
- Integrated multiwatt electronic ballasts enable the optional use of 28 W or 54 W lamps for a flexible adjustment of the lighting level to changing room and workplace requirements
- Integrated EnOcean wireless technology 868 MHz, lighting level can be set wirelessly (type RF)
- Integrated DALI MULTleco PIR (passive infrared) light management system with daylight and presence monitoring


ORDER NUMBERS



Pendant uplighter 228/254



Pendant uplighter 235



Pendant uplighter 428/454

PENDANT UPLIGHTER TYPE FITTED WITH ORDER NUMBER

Pendant uplighter switchable	DYP 228	2 x 28 W	121 454 008
Pendant uplighter dimmable, DALI	DYP 228/D	2 x 28 W	121 456 008
Pendant uplighter PIR Taster	DYP 228/R	2 x 28 W	121 456 021
Pendant uplighter PIR wireless	DYP 228/RF	2 x 28 W	121 456 018
Pendant uplighter switchable	DYP 235	2 x 35 W	121 471 008
Pendant uplighter dimmable, DALI	DYP 235/D	2 x 35 W	121 474 008
Pendant uplighter switchable	DYP 254	2 x 54 W	121 455 008
Pendant uplighter dimmable, DALI	DYP 254/D	2 x 54 W	121 457 008
Pendant uplighter PIR Taster	DYP 254/R	2 x 54 W	121 457 021
Pendant uplighter PIR wireless	DYP 254/RF	2 x 54 W	121 457 018
Pendant uplighter switchable	DYP 428/2	4 x 28 W	121 458 008
Pendant uplighter dimmable, DALI	DYP 428/D	4 x 28 W	121 460 008
Pendant uplighter PIR Taster	DYP 428/R	4 x 28 W	121 461 020
Pendant uplighter switchable	DYP 454/2	4 x 54 W	121 459 008
Pendant uplighter dimmable, DALI	DYP 454/D	4 x 54 W	121 461 008
Pendant uplighter PIR Taster	DYP 454/R	4 x 54 W	121 461 020

ACCESSORIES


ORDER NUMBER

PENDANT UPLIGHTER PIR WIRELESS	Battery-free wall transmitter	330 633 010
--------------------------------	-------------------------------	-------------


TECHNICAL DATA

TYCOON SURFACE-MOUNTED LUMINAIRE

TWO-FLAME



CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	2 x fluorescent lamps T 16 28 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	63 W
MAINS LEAD	direct power supply
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
LUMINAIRE EFFICIENCY	with cover 69 %
GLARE PROTECTION	light-amplifying micro prism
LIGHT DISTRIBUTION	symmetrical; direct proportion 76 %; ceiling illuminated sideways



Surface-mounted luminaire


SPECIAL FEATURES

- Suitable for ceiling heights of less than 2.40 m
- Ceiling illuminated sideways
- Vertical and horizontal wall mounting possible
- Luminous power switchable, dimmable, DALI

ORDER NUMBERS

SURFACE-MOUNTED LUMINAIRES TYPE FITTED WITH ORDER NUMBER

Surface-mounted luminaire switchable	DYD 228	2 x 28 W	121 526 001
Surface-mounted luminaire dimmable, DALI	DYD 228/D	2 x 28 W	121 526 011




Surface-mounted luminaire


TECHNICAL DATA

TYCOON COMFORT/CLASSIC WALL-MOUNTED LUMINAIRE


TWO-FLAME



efficient^{light}



Wall-mounted luminaire comfort



Wall-mounted luminaire classic

CONNECTED LOAD	230 – 240 V; 50/60 Hz
FITTED WITH	2 x compact fluorescent lamps TC-L 55 W
WORK EQUIPMENT	electronic ballast
POWER CONSUMPTION	approx. 117 W
MAINS LEAD	direct power supply
MATERIAL HOUSING	aluminum/Plastic, painted silver metallic
LUMINAIRE EFFICIENCY	with cover 73 % (COMFORT), 67 % (CLASSIC)


SPECIAL FEATURES

- Removable side part and screen for easy changing of lamps and easy cleaning
- Luminous power switchable, dimmable, DALI

ORDER NUMBERS

TYPE

ORDER NUMBER



Wall-mounted luminaire

COMFORT

LIGHT DISTRIBUTION	Symmetrical; direct proportion approx. 27 %, indirect proportion approx. 73 %	
GLARE PROTECTION	Light-amplifying micro prism, medium luminance on the reflector in accordance with EN 12464-1	
Switchable	DYW 255	121 395 008
Digitally dimmable DALI	DYW 255/D	121 396 008

CLASSIC

LIGHT DISTRIBUTION	Symmetrical; direct proportion approx. 17 %, indirect proportion approx. 83 %	
GLARE PROTECTION	Fine-louvre element	
Switchable	LYW 255	121 381 008
Digitally dimmable DALI	LYW 255/D	121 382 008

HEADQUARTERS GERMANY

Herbert Waldmann GmbH & Co. KG
Postfach 50 62
78057 VILLINGEN-SCHWENNINGEN
GERMANY
Telephone +49 7720 601-100
Fax +49 7720 601-290
www.waldmann.com
info@waldmann.com

FRANCE

Waldmann Eclairage S.A.S.
Zone Industrielle
Rue de l'Embranchement
67116 REICHSTETT
FRANCE
Telephone +33 3 88 20 95 88
Fax +33 3 88 20 95 68
www.waldmann.com
info-fr@waldmann.com

ITALY

Waldmann Illuminotecnica S.r.l.
Via della Pace, 18 A
20098 SAN GIULIANO MILANESE (MI)
ITALY
Telephone +39 02 98 24 90 24
Fax +39 02 98 24 63 78
www.waldmann.com
info-it@waldmann.com

THE NETHERLANDS

Waldmann B.V.
Lingewei 19
4004 LK TIEL
THE NETHERLANDS
Telephone +31 344 631019
Fax +31 344 627856
www.waldmann.com
info-nl@waldmann.com

AUSTRIA

Waldmann Lichttechnik Ges.m.b.H.
Gewerbepark Wagram 7
4061 PASCHING/LINZ
AUSTRIA
Telephone +43 7229 67400
Fax +43 7229 67444
www.waldmann.com
info-at@waldmann.com

SWEDEN

Waldmann Ljusteknik AB
Skebokvarnsvägen 370
124 50 BANDHAGEN
SWEDEN
Telephone +46 8 990 350
Fax +46 8 991 609
www.waldmann.se
info@waldmann.se

SWITZERLAND

Waldmann Lichttechnik GmbH
Benkenstrasse 57
5024 KÜTTIGEN
SWITZERLAND
Telephone +41 62 839 1212
Fax +41 62 839 1299
www.waldmann.com
info-ch@waldmann.com

UNITED KINGDOM

Waldmann Lighting Ltd.
Holme Well Road
Middleton
LEEDS LS 10 4TO
WEST YORKSHIRE
UNITED KINGDOM
Telephone +44 113 2775662
Fax +44 113 2775775
www.waldmann.com
enquiries@waldmannlighting.co.uk

USA

Waldmann Lighting Company
9, W. Century Drive
WHEELING, ILLINOIS 60090
USA
Telephone +1 847 520 1060
Fax +1 847 520 1730
www.waldmannlighting.com
waldmann@waldmannlighting.com

CHINA

Waldmann Lighting Shanghai Pte. Ltd.
Part A, No. Five Normative Workshop
199 Changjian Road, Baoshan
SHANGHAI, P.R.C. 200949
CHINA
Telephone +86 21 5169 1799
Fax +86 21 3385 0032
www.waldmann.com
s.lo@waldmann.com.cn

SINGAPORE

Waldmann Lighting Singapore Pte. Ltd.
168, Jalan Bukit Merah, #04-09B,
Connection One, Tower 3
SINGAPORE 150168
SINGAPORE
Telephone +65 6275 8300
Fax +65 6275 8377
www.waldmann.com
sales-sg@waldmann.com